



DESORB 2007

Absorbent tubulars

FEATURES

Absorbent in cellulose fiber that absorbs water, oil, waste and any other non-aggressive fluid quickly and easily.

The **DESORB 2007** is packaged in 120x8 cm tubulars.

The tubulars can be connected together to form barriers of any length and adapt to any shape. They advantageously replace the loose materials in the task of preventing and solving problems of dispersion of liquids in the workplace, as they can be recovered, after use, with extreme ease and safety, without the need to use blades or brooms.

They are irreplaceable to create a "barrier" around machines and equipment that have the problem of dispersion of liquids and limit disposal costs compared to many bulk materials because, with the same amount of liquid absorbed, they have a final volume reduced by 10 times and a weight of 50%.

CHEMICAL/PHYSICAL DATA

Composition:	cellulose
Flammability:	160 °C
Volume:	5 Lt
Weight:	400 gr
Absorbent power:	5 lt cad.
Packaging:	20 pz / st

HOW TO USE

DESORB 2007 tubulars must be in direct contact with fluids and must NOT be placed on sawdust or residues of powders or granules. During transport and storage the material inside can be compressed or arranged in a disorderly way: for greater product efficiency, it is recommended to shake the **DESORB 2007** tubing to make it as uniform as possible.

APPLICATIONS

- Containing liquids during racking.
- Protection against oil spills, cooling solutions and process liquids from all types of machinery. The **DESORB 2007** tubulars are placed at the base of the machine, taking advantage of the fact that they are flexible and adaptable to any shape
- On work benches to contain any spills from maintenance equipment.
- As a containment ring under the source of purges, valves and fittings with an uncertain seal.

