



KEFLON SPRAY

Lubricating – PTFE release agent

FEATURES

Spray products based on **PTFE** (Poly TetraFluoroEthylene) technology. Available in two versions:

KEFLON LUBRICATING

White lubricating containing Poly Tetra-Fluoroethylene dispersed in synthetic oil. The product not spot, not strain, and not evolve in dry film. **KEFLON LUBRICATING** show optymal protection and anti wear properties.

Produce an important reduction of twisting stress and resists to wide range of temperature excursion. (-20/+140 °C)

- Conveyors in steel, of the type to tape and the type to seams.
- Food and beverage industry machinery
- Alimentary systems and machinery of various type.
- Plastic gear, locks, hinges, machinery way.
- Clips of batteries, antennas car radio, fishing equipment.
- Wood industry (blade of different type, worktops and runways)
- Printing presses (benders, cutter, tops of print)
- Machinery mechanisms lubrication.

Product code: **K00175S0**



KEFLON RELEASE AGENT

In this version the product form a dry film containing **PTFE**. This film show very good anti adhesion properties and also good chemical resistance towards substances and chemical products of common use. Film with property of release agent it does not show alterations for contact with oils, grease and detergents.

KEFLON SPRAY is indicated for all applications needed of dry and thin film with excellent anti adhesion properties.

- Release agent for plastic and the leather industry.
- Lubricating for runways
- Lubricating for gasket

Product code: **K00179S0**