



KEMPERSOLV W

Degreaser emulsifiable in water

FEATURES

Emulsifiable degreasing detergent in water for the removal of heavy dirt, oils, greases and carbon deposits.

- It is a product completely free of chlorinated and aromatic substances and therefore represents a significant improvement for the health of the operators, without containing any toxic component under normal conditions of use.
- The product can be stored without particular precautions as it is perfectly stable in a wide temperature range (from - 22 ° C to + 60 ° C).
- It hasn't corrosive effects on aluminum, magnesium, titanium, steel and stainless steel alloys.
- It doesn't cause cracking or breakage of plastic materials.

CHEMICAL – PHYSICAL DATA

Physical state	: liquid
Color	: amber
Flammability	: + 61°C
pH (at 25°C)	: 8.5-9.5

HOW TO USE

The **KEMPERSOLV W** can replace the various solvents commonly employed in a particular industrial degreasing both metallic and synthetic material.

In these cases it is very economical, as it can be diluted in water, not inflammable, not annoying because of the vapors and finally disposable with fewer problems and with considerably lower costs.

It can be used for all hard surfaces, such as metal, painted or plastic material. Use as it is or, more conveniently, diluted with water:

Cleaning of light dirt: dilute 1 part of product in 15 parts of water.



Normal cleaning: dilute 1 part of product in 9 parts of water.

Cleaning of heavy dirt: dilute 1 part of product in 4 parts of water.

- 1- We recommend rinsing the surface to be cleaned with water.
- 2- Apply the detergent emulsion with a sponge, a mop or a sprayer.
- 3- Leave for 5-10 minutes and rub with a sponge or a mop..
- 4- Rinse thoroughly.
- 5- The product can be applied to the dilutions indicated with pressure spray systems.

The product has proved particularly effective in the cleaning of aircraft that have been in contact with sea water. For safe use, see the safety data sheet

STORAGE

The product is stored in original containers for a period of no less than 3 years.

SPECIFICATIONS

A-A-59921

**MIL-C- 43616C (Class 1) – obsoleta-
CLEANING COMPOUND. AIRCRAFT
SURFACE**