



LUBRO DRAW

Fluid for drawing

CHARACTERISTICS

LUBRO DRAW is a specific formulation to be used as a lubricant additive in the operations of:

- SHEARING
- DRAWING
- FOLDING
- DRAWING

The product has the function to create a strong and tough film between the working material and the tool, in order to facilitate sliding and to prevent seizures and scuffs.

LUBRO DRAW is a very fluid and fast-evaporating, so it eliminates the final degreasing of pieces. Is therefore the most suitable product for laminations, switch covers, small pieces of various equipment and light general componets.

The advantages that are obtained using the **LUBRO DRAW** are the following:

- ✓ Is used on all metals (aluminium, brass, copper, steel, stainless steel, etc.).
- ✓ Leave the pieces protected, but clean and oil-free.
- ✓ Obviates degreasing final before any treatments painting, plating or welding.
- ✓ Compatible with any metal.
- ✓ Odor less



PHYSICAL-CHEMICAL DATA

Physical state	: clear liquid
Color	: color less
Odor	: odor less
Density	: 0,76 Kg/l
Viscosity	: 1,6 Cst @ 25°C
Flash point	: 60°C

METHODS OF USE

LUBRO DRAW is used as such and can be applied by dipping, spraying, brushing, or drip circuit with automatic dosing. More recently introduced the application by means of the **MICRO LUBRICATION COOLANT**.